



Quick Insertion Guide:




IDENTIFY EARPIECES

marked (R) for right and
(L) for left




ALIGN EARPIECES

at the ear canal, with cord
facing forward & slightly
downward



INSERT EARTIP

into ear canal and rotate
earpiece backwards &
into position



CHECK FOR SEAL

place finger over the outside
surface of the ambient filters
and verify noise isolation


Detailed Insertion Instructions *(refer to figures on cover page)*

Before inserting the monitor, turn down the volume on your sound source and either drape the cord over your shoulders and down your back, or run the cord down in front. The monitors are marked (R) for the right ear, (L) for the left. If you have selected a foam eartip, compress the foam by rolling it between your fingers (fig. 1). With the body of the monitor toward the back of your ear and the cord facing forward, insert the eartip into your ear canal before the foam expands back to its original shape (fig.2). If you have trouble inserting the monitor, reach over your head with your opposite hand and gently pull up and back on the top of your ear before inserting the eartip. This helps straighten your ear canal and may allow for easier insertion. The monitor cord should run over and behind your ear. Hold the monitor in place for 5 to 10 seconds to allow the foam to expand and conform to the shape of your ear canal (fig. 3).

The unique ambient feature of your in-ear monitors requires that the earpiece be properly sealed in your ear canal. To verify, place your fingertips over the “W” logo on the ambient filters. Both the left and right filter should be blocked at the same time. This should result in a dramatic change in your ability to hear what is around you and verify that the earpieces are properly seated and sealed.

Once the monitors and cords are comfortably in place, slide the cable zipper up to the base of your skull (not too snugly, as this may cause discomfort). This will limit cable movement and help ensure that your monitors stay in place during use.


Cable Removal



HOLD FIRMLY & REMOVE AT STRAIGHT ANGLE


Hold the earpiece and cable firmly with each hand (close to the connection) and remove the cable by pulling at a straight angle from the socket. *Do not pull from the wire!*

Cable Replacement




CHECK

if the cable is for the left or right monitor



MATCH

the cable to appropriate monitor



INSERT

the cable into the monitor by pushing directly into the socket

AM Pro Care + Maintenance

Here are a few simple guidelines that can greatly increase your listening enjoyment and the lifespan of your AM Pro monitors:

- Always store your monitors in the provided case.
- In case of poor sound quality due to earwax in the sound bore, use the included wax removal loop to carefully remove the earwax. Never use any other object to attempt to remove the earwax as this may result in damage to the monitors and will void the warranty.
- Do not use the cord to remove the monitors from your ears. This may cause damage to the cord and result in poor performance. Damage of this nature is not covered by the warranty.
- Do not expose your monitors to temperature extremes.
- Avoid strong impacts to your monitors.
- Wipe down your monitors after each use.
- Never immerse your monitors in water.
- You should use extreme caution or temporarily discontinue use in potentially hazardous situations.
- Don't use while operating a motorized vehicle as it may create a traffic hazard & is illegal in many areas.

Please Note: Moisture in your monitors can cause temporary performance issues. Do not insert your monitors if your ears are wet. Always dry your ears completely before inserting your monitors. Should you inadvertently allow water or perspiration into the monitors and they quit working, allow to dry completely before attempting to use again. Minor moisture build-up should dry out and not affect long-term performance. Extended exposure to moisture or submersion will result in permanent damage (not covered by the warranty).

Remember, personal hearing protection is your responsibility!

The use of any monitor offers benefits and risks. Westone Audio's AM Pro monitors can lower ambient sound levels approximately 12dB when properly worn. However, the performance capabilities of the monitors can allow the user to negate the benefits of hearing protection from ambient sound. Do not turn up the volume so high that you can't hear what's around you.

If everything sounds muffled or you hear ringing or buzzing after using your monitors, your ears are trying to give you a warning! These are symptoms normally associated with a condition known as Temporary Threshold Shift and are an indication of conditions that could lead to permanent hearing loss.

Noise-induced hearing loss is preventable but often undetected until it is too late. Westone Audio and the Electronic Industries Association's Consumer Electronics Group recommend you avoid prolonged exposure to excessive noise. Used responsibly, your AM Pro monitors can help prevent noise-induced hearing loss. If you have questions, contact your audiologist or hearing care professional.

While no two individuals' hearing sensitivity is exactly the same, there are established safety guidelines for sound levels versus time of exposure. The chart below is based on OSHA's (Occupational Health and Safety Administration) exposure information for industry. *Remember that these guidelines are based on average hearing sensitivity. Your sensitivity may be above or below these levels.*

dB Level	MAXIMUM Exposure Time
85	8hr
90	4hr
95	2hr
100	1hr
105	30mins
110	15mins

Limited Product Warranty

Westone Audio warrants this product to be free of defects in material or workmanship for a period of two (2) years from the date of original retail purchase. This warranty is available only to the original purchaser, and only if purchased from an authorized Westone Audio distributor or reseller. If your product is found to be defective during the warranty period, Westone Audio will, at its sole option, either repair the product or replace the product with a new or factory reconditioned or substantially equivalent model. This limited warranty does not apply to loss, theft, or any defects attributable to damage beyond the reasonable control of Westone Audio including damage caused by abuse, misuse, misapplication or modifications performed by anyone other than Westone Audio. This warranty applies only to the external shell of the product, the internal components and cable. The carrying case, cleaning tool, any adapters and other included accessories are warranted for 90 days. Tips are not covered by the warranty.

Repair/Replacement Warranty

This Limited Warranty shall apply to any repair, replacement part or replacement product for the remainder of the original warranty period or for ninety (90) days, whichever period of time is greater. Any parts or product replaced under warranty will become the property of Westone Audio.

Requesting Warranty Support

If your product is not functioning properly, first ensure that the sound bore is not blocked by earwax and that the unit is completely dry. Performing these simple troubleshooting steps could solve the problem and eliminate the need for factory service. Valid warranty claims are generally processed through the point of purchase during the first thirty (30) days after retail purchase.

United States & Canada

If it is necessary to return your product to Westone Audio for warranty or post-warranty service, contact Westone Audio to request a return merchandise authorization (RMA) number. You may call 949-793-8136 or go to <https://westoneaudio.com/productreturn> to submit a Product Return Request Form. Please note you will be required to submit reasonable

proof of purchase date, ownership, and that the product was purchased from an authorized Westone Audio retailer. Once you receive your RMA number, package the product securely to prevent damage in transit, include the documentation, and send prepaid and insured through a trackable shipping carrier to:

Westone Audio, Inc., Attn: Music Returns Dept., 14301 FAA Blvd, Suite 105 Fort Worth TX 76155

Westone Audio will be responsible for shipping to the consumer after warranty repair/replacement only. The customer is responsible for all shipping/handling charges related to returning the product to Westone Audio.

International

The warranty on this product if it is sold to a consumer outside of the United States and Canada shall comply with applicable law. To obtain warranty service, contact the dealer from which you purchased or the distributor that supplied this product. Additional charges and limitations may apply. If purchased through an international location without a Westone Audio distributor, or an authorized Westone Audio retailer (but not through the local distributor or distributor's network) contact Westone Audio directly (*see United States & Canada instructions above*)

Limitation of Liability

Westone Audio disclaims any and all implied warranties, warranties of merchantability and fitness for a particular purpose to the maximum extent permissible by law. Westone Audio shall not be liable for any special, incidental or consequential damages caused by the use, misuse, or inability to use this product. If purchased under a government contract, those contract terms supersede terms stated herein. In some locations, implied warranties cannot be limited. Under certain conditions, these limitations or exclusions may therefore not apply to you. This warranty replaces all other warranties for this product.

Register Online Today

Complete your registration card online at: <https://westoneaudio.com/productregistration>



WESTONE AUDIO

At Westone Audio, we value your satisfaction.

If you have any questions, please contact us:

Westone Audio, Inc.

General Customer Service Phone Number: 949-793-8136

General Customer Service Email: customerservice@westoneaudio.com

Customs' Phone Number: 817-554-9708

Customs' Email: custom@westoneaudio.com

Address: 14301 FAA Blvd Suite 105 Fort Worth, TX 76155 USA

www.westoneaudio.com